



40' STACK-FOLD PL5200

The PL5200 is a bulk-fill or row-fill, stack-fold planter designed specifically for bedded irrigation and wide-row applications, offering precise singulation and accuracy to achieve even emergence for maximum yields. The PL5200 is available in 36", 38", and 40" single and

twin-row configurations. With the twin-row configuration, producers can choose the optional side-shift feature to switch between single- and twin-row planting within an hour.



INDIVIDUAL BOXES MODEL
PL5200



BULK-FILL MODEL
PL5200

FEATURES & BENEFITS



ON-BOARD SEED DELIVERY OPTIONS

The PL5200 planter offers a choice of on-row individual hoppers or bulk seed with air delivery. The 50-bushel bulk hopper is located close to the tractor to reduce the tractor's 3-point lifting requirements.



3-PT OR 2-PT WITH LIFT ASSIST

PL5200 planters can be optioned with either full 3-point mounting for tractors large enough to handle the weight or 2-point mounted with castoring lift assist wheels to help with the lifting and flotation.



EXCLUSIVE HITCH OFFSET

The optional side-shift feature helps keep the row units centered on top of the beds, yet gives twin-row models the ability to convert between single and twin row spacings in under an hour.



3-DRIVE OPTIONS

Choose between ground drive (shown), hydraulic drive, or Individual Row Control (IRC) for turn compensation and prescription map planting.



SIMPLE SEED DELIVERY

Seed distribution on bulk models is handled by a venturi system without any moving parts. This ensures reliability and simplifies cleanout.



5000 SERIES ROW UNIT

This design utilizes ductile cast parallel arms for long-term row unit stability. The 15", 4mm blades are offset 1/2" to form a perfect seed trench.

OPTIONS (see website for complete list of features & options)



SCALES

Verify seed usage to help confirm seeding rates and maximize efficiency.



ROW-MOUNTED COULTER

Inline coulters aid in row unit penetration and cut trash ahead of opener disc blades.



7" or 12.1" MONITOR

Choose between two Topcon monitor sizes.



CAMERA

ISOBUS-camera kits help producers see surroundings.

40' Stack-Fold	Working Width	Transport Width (Bulk)	Transport Height (Bulk)	Engine H.P. Required	Row Spacing	Base Weight (Single, Twin)	Seed Capacity
PL5200 12-Row Bulk-Fill	40'	24' 3"	13'	260-325	36", 38", 40",	13,950, 17,450	50 bu.
PL5200 12-Row On-Row	40'	24' 3"	13'	260-325	TR36", TR38", TR40"	12,500, 16,100	3.0 bu./row (single); 1.6 bu./row (twin)

See GreatPlainsAg.com for complete specifications.

Specifications are subject to change without prior notification. Images may not depict current or standard production models.



ADDITIONAL STANDARD FEATURES

- ISO-6 Control System
- 5000 Series Air-Pro® Meter with industry-leading singulation
- Positive air is plumbed through the frame to the meters, resulting in an ultra-clean toolbar
- Hitch-Pin Ready™: just drop the pin and go!
- Lightweight and low compaction
- Two (2) heavy-duty hydraulic fans on bulk-fill models
- One (1) heavy-duty hydraulic fan on individual-hopper models
- Wide steps w/ walkboards
- Rigid aluminum seed delivery tubes
- Unit-mounted coulters
- LED safety lighting

GREATPLAINSAG.COM