



RB37 Series

Features	Benefits
Warranty	One year parts & labor. See warranty page for complete details.
Working widths (72", 84" & 96") (1.83m , 2.13m & 2.44m)	Choice of three sizes to pick from.
35-80 hp (26.1-59.7 kW) rating	Fits a wide variety of small tractors.
Quick Hitch	Fits Land Pride Quick Hitch.
Blade angles left and right up to 45° in forward position and 30° in reverse position	Allows operator to set the blade at many angles to complete different jobs with satisfactory results. See Specifications for number of angles in forward and reverse positions.
Blade offsets left or right up to 26"(66cm)	Manually rotate main frame in 15° increments up to 45° to cover either tractor tire and to allow operators to work next to retaining walls, abutments, and curbing.
Blade tilts up or down up to 15°	(5 positions: Center, 2 clockwise, and 2 counterclockwise) Allows operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches.
17" (43.2cm) High moldboard	Rolled moldboard allows material to flow easily, which means less drag, less hp. 17" (43.2cm) High moldboard for excellent capacity.
Reversible cutting edge	For twice the life.
Parking Stand	Store unit with front of hitch off the ground, allows for easier hook-up.
Hydraulic Angling (Accessory)	Allows operator to change blade angle from the tractor seat.
End Plates (accessory)	End plates hold material in to be moved.
Skid Shoes (accessory)	Help protect from hitting low obstructions by keeping the cutting edge off the ground. Set skid shoes to clear obstructions like manhole covers and street cracks.