

LR16 & LR26 Series Landscape Rakes

Features	Benefits
Working widths: 60", 72", 84", & 96" (1.52 m, 1.83 m, 2.13 m, & 2.44 m)	Meets a wide range of customer needs.
LR16 Series: 20-40 hp (15-30 kW) LR26 Series: 25-60 hp (19-45 kW)	Fits many tractors with a Cat. I 3-Point hitch.
Quick hitch adaptable	Fits Land Pride's Quick Hitch for a quick and easy one person hook-up.
Retractable park stand	Keeps frame off the ground and makes hook-up easier.
Pivot tube 3 1/2" (9 cm)	Heavy frame tube. Heaviest in its class.
Rake height 16 1/2" (42 cm)	Can move a great deal of material.
Rake teeth support channel	Design with channel support. This design supports the rake teeth better than competitor models. Prevents teeth entanglement and keeps attachment hardware from working loose.
High carbon spring steel teeth 5/16" x 1" (8 mm x 2.5 cm)	Sized to eliminate premature bending and tooth breakage. Constructed of materials that have "memory" to spring back to shape.
Individual replaceable teeth	Makes replacing a damaged tooth quick and easy without removing all of the teeth.
Angle 7 positions	Versatility in operation. Vary how much material to move.
Hydraulic angle kit (Accessory)	Allows the operator to change rake angle from the tractor seat.
Dual gauge wheels (Accessory)	Gives operator better depth control. Wide & narrow wheels available.
Flip-down grader blade with end plates (Accessory)	Enables the rake to perform light blading duties for moving and leveling dirt as well as other materials. Grader blade can be flipped up when not in use.
Rear blade attachment (Accessory)	The rake assembly can be removed from the main frame and a Rear Blade attached to give the Land Pride Rake versatility.