

LR37 Series Landscape Rakes

| Features | Benefits |
|--|---|
| Two working widths | Covers tire tracks and allows user to cover large areas in less time. |
| Tractor horsepower: 30-80 (22-60 kW) | Fits many tractors with a Cat. I or Cat. II 3-point hitch. |
| Quick hitch compatible | Fits Land Pride Quick Hitch for a quick and easy one person hook-up. |
| Retractable parking stand | Keeps frame off the ground and makes hook-up easier. |
| Pivot shaft: 2 1/2" (6.4 cm) | Heavy-duty shaft. Heaviest in its class. |
| Rake height: 16 1/2" (41.9 cm) | Can move a great deal of material. |
| Rake teeth support channel | Design with channel support. This design supports the rake teeth better than competitor models. Prevents teeth entanglement and keeps attachment hardware from working loose. |
| High-carbon spring steel teeth 5/16" x 1" (8 mm x 2.5 cm) | Sized to eliminate premature bending and tooth breakage. Constructed of materials that have "memory" to spring back to shape. |
| Individual replaceable teeth | Makes replacing a damaged tooth quick and easy without removing all of the teeth. |
| Rake angle, 5 positions | Versatility in operation. Vary how much material to move. |
| Rake offset, 7 positions | Versatility in operation. Allows the unit to work closer to objects on the side the rake is of set towards. |
| Dual gauge wheels (Accessory) | Gives operator better depth control. Wide & narrow wheels available. |
| Flip-down grader blade with end plates (Accessory) | Enables the rake to perform light blading duties for moving and leveling dirt as well as other materials. Grader blade can be flipped up when not in use. |
| Rear blade attachment (Accessory) | The rake assembly can be removed from the main frame and a rear blade attached to give the Land Pride rake versatility. |
| Hydraulic angling (Accessory) | Allows operator to change rake angle from the tractor seat. |