

HRL35 & HR35 Retractable Series

Features	Benefits
1/2" Heavy side panels	Thick end panels guard against abrasion.
Hydraulic shank tube	Hydraulic shank tube makes for efficient use of time.
Clevis-type lower 3-point hitch	Allows for easier hook-up of the tractor's lower draft arms.
3 Position heat treated spring steel shanks	Positions set for deep to shallow settings. Heat-treated for longevity.
Roll-formed moldboard	Roll-formed moldboard keeps materials flowing which puts less drag on the box scraper, resulting in lower hp requirements and faster working conditions.
Heat treated dimpled on tips	Easy to replace tips that are heat treated for toughness.
Heat-treated, reversible and replaceable cutting edges	Heat-treated for hardness. Reversible so both edges can be used before replacing the cutting blades.
Hinged rear backfill blade. Fixed or floating	Rear backfill blade can be in float or fixed position. For packed down grade, level grade or rough grade
Warranty	One year parts & labor.
Category I & II 3-point hitch	Fits a wide variety of tractors.
Fits Land Pride Quick Hitch	Quick and easy attaching without leaving tractor seat.
Transport lock on shank tube	Heavy-duty shank lock to keep shanks locked into place during transport.
Knurled bushings in upper and lower hitch	Work done with retractable box blades is done forwards and backwards. Bushings at hitch points eliminate premature wear.
Heavy shank bumpers	A 3/4" square steel bumper is located behind each shank for additional reinforcement.
Accessories	
Check valve	Prevents shanks from drifting down.