

MR15 & HR25 Series (Retractable)

Features	Benefits
3/8" Heavy side panels	Built heavy to handle the tough jobs.
Mechanical vertical lift shank tube or hydraulic pivot shank tube	Retractable mode can be purchased with manual or hydraulic option.
Clevis type lower 3-point hitch	Allows for easier hook-up of the tractor's lower draft arms.
4 Positions heat treated spring steel shanks	Offers flexibility for deep to shallow settings and Heat-treated for longevity.
Working widths	MR1572 = 72" HR2572 = 72"
HP range	MR1572: 20-40 hp 4 wheel drive; 30-50 Hp 2 wheel drive HR2572: 30-60 hp 4 wheel and 2 wheel drive
Roll-formed moldboard	Roll-formed moldboard keeps materials flowing which puts less drag on the Box Scraper, resulting in lower hp requirements and faster working conditions.
19" High MR1572 moldboard 21" High HR2572 moldboard	High material capacity
Heat treated dimpled on tips	Easy to replace tips that are heat treated for toughness.
Heat-treated, reversible and replaceable cutting edges	Heat-treated for hardness. Reversible so both edges can be used before replacing the cutting blades.
Rear backfill blade	Rear backfill blade allows for backfilling trenches or foundations.
Warranty	One year parts & labor.
Category I 3-point hitch with Quick Hitch capability	Fits a wide variety of tractors. Quick hitch capability allows for easy hook-up.
Positive Locking System	Shanks are kept in the up or down position with a positive locking system. This keeps the scarifier bar from bouncing in transport, and tight during field use.
Heavy duty Shank bumpers MR1572 HR2572	3/4" x 7/8" U-shaped steel bumpers are built tough to support the shank load. 1/2" Square steel bumpers behind each shank provides additional reinforcement.