

RCR15 Series

Features	Benefits
Surpassed rugged industry standards	All Land Pride cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Cat. 3 driveline with shear- bolt	Shear bolt offers maximum driveline protection.
Cat. 3 driveline with 2-plate slip-clutch	Slip-clutch driveline offers convenience for continual work.
Floating top link	Provides for easy hook-up. Permits deck to follow the terrain for an even cut. Two hole position to allow greater lift leverage for smaller tractors.
Fully welded deck	Robotic welded. Adds additional strength.
Round back design	Helps discharge grass better than enclosed or partially enclosed cutters.
Cutting height	1" - 9" cutting height for wide range of cutting conditions.
Full length skid shoes	Provides sidewall reinforcement and full protection to bottom of sidewall.
1/2" x 3" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
Splined blade bar hub	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
10 Gauge stump jumper	Allows cutter to slide over obstructions protecting the gearbox output shaft.
High blade tip speed	Ensures clean cut. 42" = 11,459 fpm 48" = 13,090 fpm
Laminated tailwheel	Laminated material is long lasting in rough conditions.
Solid rubber tailwheel	Can't go flat.
Heavy-duty spindle on the tailwheel	Tailwheel take a beating, 1 1/4" spindle gives the strength to protect tailwheel assembly.
Guarding	Protect against flying debris. Customer can choose to include rubber on the front and rear.
Driveline holder	Keeps driveline up out of dirt. Easier hook up of driveline.