

### AP-PS2072 & AP-PS2086

Features	Benefits
<b>3-Point &amp; Quick Attach compatible</b>	Allows for hooking up to tractors or skid steers.
<b>Cat. 1 Hitch</b>	Fits Land Pride Quick Hitch for easy one person hook-up to tractor.
<b>72" (1.83 m) &amp; 86" (2.18 m) Seeding width</b>	Perfect size for landscape market. Sized for smaller areas such as between the curb and sidewalk or the new community park.
<b>Approximate machine weight</b>	AP-PS2072 = 1,464lbs (664.1 kg) & AP-PS2086 = 1,677lbs (760.7 kg). Heavy weight helps seed to soil contact.
<b>Lift hooks</b>	Lift hooks on each side of the seedbox to attach chain or strap to for easy loading and unloading.
<b>Heavy-duty lid with stay open support</b>	Lid is precision fit to keep seeds dry and rodents out and they won't buckle or slam shut in high winds.
<b>Seed splash guard</b>	Seedbox lid has a guard to prevent seed from being spilled between lid and box.
<b>Water tight Seedbox</b>	All-welded seedbox construction. Keeps moisture out of the seedbox.
<b>Easy seed box clean out</b>	Seed flute is designed for easy clean out.
<b>Large seedbox capacity</b>	One bushel per foot. Keeps filling to a minimum and increases productivity.
<b>Seed box agitator</b>	Eliminates bridging of seed.
<b>Bi-directional seed cups</b>	Allows for seeding, traveling forward and in reverse.
<b>Wind guarded seed drop</b>	Protects the seed from being blown away by windy conditions. Ensures constant placement of seed across the whole width of the machine.
<b>Seed rate adjustment</b>	Easy adjustment of seed rates. Lever position is located on seed rate chart.
<b>Seed rate decal</b>	Positioned on lid. Easy access to seed rate information.
<b>Ground driven metering</b>	Rear packer rollers are in constant contact with the ground to ensure consistent metering of seed. Seed metering stops automatically when rear packer is raised off the ground.
<b>Cast iron packer rollers</b>	9" (22.9 cm) diameter rings are used to crush the clods and pack the seed in to promote seed to soil contact.
<b>Tire track removers</b>	Coil spring tine track removers keep their shape; allows tractor tire(s) to be scratched out.
<b>#40 Roller chain</b>	All drives utilize #40 roller chain for smooth running.
<b>Spring loaded chain idler</b>	Spring loaded idler keeps constant pressure on chain so seeding rate is consistent.