

AFM3011 All-Flex Grooming Mowers

Features	Benefits
Counter blade rotation on center and right-hand deck	Spreads grass clippings more evenly. Wing decks throw grass away from the rear deck. Rear deck doesn't get covered up or bogged down by cut grass. Prevents robbing tractor horsepower.
5'-7" (1.7 m) Transport width	Meets most city/county codes for transport width.
6" (15 cm) Deck overlap	Eliminates skipping when going into a tight turn.
10'-11" (3.5 m) Cutting width three 48" decks	Sized right for golf courses, cities, schools. Small decks give excellent flexibility.
Sleek frame design, including single beam hitch and compact deck overlap	Design allows operator to make tighter turns without leaving windrows and skips. AFM virtually becomes a zero turn mower. (Oversized tires may not allow this.)
Automatic transport wing locks	When wings are raised in the full transport position, the wings lock in place. No need to get off the tractor to lock. Pull rope from tractor seat to un-lock.
Optional Hydraulic Transport Locks	Transport locks can be released easily from the tractor seat while operating the same tractor control lever that folds and unfolds the mower decks. Eliminates pulling a rope to release transport locks.
18" Transport tires with tapered roller bearings	Transport tires offer smooth roading and less grass compaction. Allows grass to stand up. Tapered roller bearings offer longevity.
Removable transportation tire spindles	Allows a spindle to be replaced by simply removing one bolt.
Back wheels on side decks in line with transportation tires	Allows tighter turns without skips.
Zero turn radius	Sleek frame design allows operator to make tighter turns without leaving windrows or skips. The AFM virtually becomes a Zero Turn Mower.
Rigid rear side deck tires.	Rigid wheel yokes holds hills and slopes better.
10" Solid rubber deck tires	Solid rubber won't go flat.
Square tube gauge wheel arms	Gives the mower gauge wheel arms a great deal of "hidden" strength.
Low pivot points on deck	The lower the pivot points are to the ground, the more side to side swing, allowing for excellent flotation from each deck.
Deflectors built into mower decks	Safety features meet ANSI standards. Many competitors use chains for protection. Once chains are removed the unit does not meet ANSI specifications.
Rear discharge	Even dispersal, discharged items are aimed downward. No rear chains are needed, which tend to clump damp grass.
Rounded front deck edges with no protruding skid shoe	Helps protect trees and other obstacles.
1/4" (6 mm) Front edge & all-welded seams	Provides extra durability.
Cat. 3 equal angle main driveline	Equal angle main driveline allows for tighter turns without harming U-joints in driveline.
Shear bolt protection	Guards against premature gearbox failure. Protects mower deck spindles.
Cat. 3 wing drivelines	Designed to withstand start-up torques.
ABS guards	No paint to scratch off, lighter weight, no rattling or rust.
Heavy gearbox mounts on center and side mower decks	Handles start-up torque better.
Gearbox Horsepower Rating	30-55 hp (22-41 kw)
Gearbox warranty	Three year limited gearbox warranty. Demonstrates our confidence in the gearbox's quality and lasting performance.
Sealed for life blade spindle bearings	No blade spindles to grease means no guards to remove to grease blade spindles.

AFM3011 All-Flex Grooming Mowers

Features	Benefits
Middle spindle sits towards the back of the mower deck.	Uses less horsepower and allows material to escape the mower deck easier. The discharge of material is more even. Design eliminates windrowing.
Spring loaded idlers	Applies constant tension to belt to run efficiently.
High blade tip speed	Lifts grass up for a clean cut and efficient discharge of material. Tip speed rates are as high or higher than the competition.
Choice of Blade (Medium lift standard) Others available thru parts dept.	<p>Low Lift - Highly recommended in sandy soils where lifting isn't crucial. Disturbs the soil very little, allowing blades to wear longer.</p> <p>Medium Lift - Medium suction for lifting grass. Requires less horsepower than high lift.</p> <p>High Lift - Greatest suction for lifting grass before cutting. Can take higher horsepower in tall dense grass. Not recommended in sandy soils.</p> <p>Mulching - Perfect for leaf mulching.</p>