

Type of Lubrication: Multi-purpose Grease

**DB2660 & DBM2660 Models**

Features	Benefits
<b>Tractor HP Range</b>	Designed for 75 minimum HP tractor with minimum weight of 7,000 lbs.
<b>Gearbox HP Rating</b>	150 HP
<b>3 Point Design</b>	Does not require a dedicated tractor. Three point hook up is easy to hook up and remove from tractor.
<b>Cutter Deck Visibility</b>	Visibility of the cutter deck is captured from the operator’s seat. Easy to see operation. Operator does not have to look behind.
<b>Factory Assembled</b>	Arrives ready for the customer, saves time and money. (Excluding gauge wheel options and fluids.)
<b>Grease Ports</b>	All grease ports are easily accessible for servicing.
<b>10' Transport Width</b>	Folds up close to the tractor. No weight brackets or decks hanging away from the tractor. Typically, not much wider than the tractor, which means safer transporting.
<b>Extension Arm Design</b>	One cylinder used to adjust extension arm horizontally 32" is easy to operate.
<b>Long Horizontal Reach</b>	Good access for reaching vegetation far away from the tractor.
<b>Above Grade Vertical Reach</b>	Good access for reaching up embankments and cutting low over hanging limbs.
<b>Below Grade Reach</b>	Good access for reaching down embankments.
<b>175 Degree Deck Rotation Angle</b>	Cutter head can be positioned to reach different angles.
<b>Cat. 2 &amp; Cat. 3 with Quick Hitch 540 rpm or 1000 rpm</b>	Fits a wide variety of tractors.
<b>35 Gallon Oil Reservoir</b>	Large reservoir maintains optimum fluid temperatures and also serves as counterweight.
<b>1" Cutting Capacity</b>	Good for trimming brush.
<b>High Blade Tip Speed</b>	15,600 FPM tip speed means cleaner cutting.
<b>One Parking Stand</b>	Easy to adjust 3-point hitch level for unhooking tractor.
<b>In-line Filter</b>	Cleans hydraulic fluid before it re-enters the reservoir.
<b>Shut-off Valve</b>	Permits maintenance with minimum oil loss.
<b>Built-in Auxiliary Weight Rack on Left Side</b>	Suitcase weights can be added to left side for balance. Able to choose the weight bracket to match various types of suitcase weights.
<b>Oil Pressure Gauge</b>	Easily monitor oil pressure for optimum performance of unit.
<b>Pressure Relief Valve</b>	Protects against high hydraulic fluid pressure.
<b>Gauge Wheels Option</b>	Deck floats on gauge wheels eliminating frequent deck positioning and vigilant watch for changes in ground contour under the tractor and/or deck.
<b>SMV Mounting Socket (Standard)</b> <b>SMV Sign (Accessory)</b>	SMV mounting socket receives most SMV signs equipped with a mounting blade for ease of attachment and removal when transporting on a truck or trailer. SMV sign is offered as an accessory when the tractor’s SMV sign and mounting blade does not fit the cutter’s standard SMV mounting socket.