

HD25 & HD35 Series

Features	Benefits
3-Point mount Cat. I & II hitch	Fits a wider variety of tractors by fitting Cat. I & II
Bucket mount	Easily bolt mounting plate to the side of the front loader bucket, and use the bucket to help push auger into the ground
Skid/loader hitch mount	Fits skid steer & tractor front loaders with skid/loader hitch mount. Auger can be mounted in the center or offset to the right. Loader arms can help push auger into the ground.
3-Point yoke: 2 7/8" O.D.	3/16" Wall thickness for strength and durability.
3-Point boom: Reinforced 3 1/2" O.D.	7/32" Wall thickness reinforced with 3/8" x 2" bar makes for a strong boom.
Large selection of augers	Variety of Dirt Auger and Rock Auger sizes and styles to suit many applications.
Large selection of Bolt-on Rock Heads (accessory)	All sizes of Land Pride HD25 and HD35 Pengo Dirt Augers can be converted to Rock Augers with this accessory.
Auger flighting	Constant thickness on 1/4" flighting verses tapered.
Replaceable cast alloy steel point with 3 fishtail tips	3 Fishtail tips will last 50% longer than 2 tips. Cast alloy steel point can easily be replaced when worn or damaged.
Replaceable dual angle teeth	Dual angle teeth can be changed from 40° to 50° to increase attack angle. Teeth can easily be replaced when worn or damaged.
25 Series	Use with hydraulic systems that pump at 5 –12 GPM, at 1500 – 3500 PSI.
35 Series	Use with hydraulic systems that pump at 10-25 GPM, at 1500 – 3500 PSI.
2" Output shaft	2" Handles torque loads that can be transmitted from hard ground. Fairly standard size for the industry, fits many competitive augers.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Hydraulic hose	Standard on 3-point Post Hole Diggers and skid/loader mount Post Hole Diggers. Optional on bucket mount Post Hold Diggers due to distance varying on tractor models.
6", 9", 12", & 18" Diameter auger options	Wide range of auger diameters to choose from.
48" Auger Length	Auger is provided in industry standard length.