

SRT62 & SRT76

Features	Benefits
6" Offset capability	Offset allows operator to till closer to fences, buildings, sidewalks, and other objects. Hook skid steer hitch to the left side of tiller hitch plate to side shift tiller 6" to the right. Hook skid steer hitch to the right side of tiller hitch plate to center tiller on the skid steer.
Depth indicator	Operator can tell how deep the tiller is working in the soil without leaving the seat.
Hydraulic depth control	Operator can rotate skid steer hitch on the tiller skid shoes to any depth indicated on the depth indicator. Operator does not have to adjust skid shoes to set tiller depth.
Rotor can be operated forward or reverse	Allows operator to choose forward or reverse tilling by reversing hydraulic flow. Reverse tilling is good for breaking up hard ground and covering trash.
SRT62 offers a choice between low flow or high flow SRT76 is offered in high flow	Low flow (14 to 23 gpm) and high flow (23 to 42 gpm) allow these tillers to fit a wide variety of skid steers.
Case drain hose	Reduces back pressure on motor which increases power for tilling and protects outer seal.
1/4" Heavy duty deck and 3/8" heavy duty end plates	Deck and end plates are built tough.
Replaceable skid shoes	Keep bottom of end plates from wearing.
Bolt in spiral design rotor	Reduces bouncing of tiller.
Bolt-on tiller tines designed to attach with one bolt per tine	Makes replacing tines fast and easy.
Bi-directional hardened boron steel tines	Tiller tines are built tough to last. Tines are sharpened on both edges to cut into the soil while operating forward or reverse. If bi-directional tines are used primarily rotating in one direction, they can be reversed (turned around) to extend their life.
Motor guard	Protects motor, fittings, and hydraulic hoses from damage caused by bumping into objects around the motor.
Adjustable scarifier shanks constructed of hardened steel	These shanks are built tough to rip up hard soil. They make tilling easier in hard soil.
Optional small flat face couplers or large flat face couplers	Fits a wider variety of skid steers.