

SSG2524 Model

Features	Benefits
Universal quick attach mounting system	For quick and easy attachment.
8" Digging depth	A good depth below the ground. Removes base of most trees.
Adjustable skid shoes	Adjustable to fit all sizes of skid steers.
Pivoting discharge deflector	Discharge deflector pivots up while cutting wheel is digging into the ground.
Welded on serrated step	Good safe step for accessing skid steer operator's seat.
High speed cutting wheel	Cuts faster with less vibration.
Permanent hose holders	Hoses aren't zip-tied to the frame. Zip ties can break over time.
Replaceable carbide cutting teeth	Cutting teeth are easy to replace. Carbide tips for extra long life.
Hydraulic hose lines	Hydraulic hoses absorb shock. Steel hydraulic lines crack from vibration.
Case drain hydraulic line	Protects against component damage.
Keyed, tapered spindle on end of hydraulic motor	Able to draw cutting wheel tight against the tapered shaft providing an excellent fit-up and less likely to shear the key off.
Cutting wheel designed with wheel puller access holes	Makes it easier to pull the cutting wheel off of the motor spindle.
Attached rain tight manual holding tube	Keeps manual with stump grinder for quick easy access. Manual won't get wet.
Offset articulating arm	Allow for optimum line-of-site from operator's seat.