

RC4620 & RCM4620 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures according to ISO 4254-13.
Factory assembled	Saves customer set-up time and money. Adjustments should always be made by dealer.
7 Year gearbox warranty*	Shows confidence in gearbox integrity. Years 6 & 7 parts only
250 hp divider gearbox 210 hp center & wing gearboxes	Rugged heavy-built gearboxes capable of handling heavy-cutting applications.
Gearbox seal protection	Gearbox bottom seal protection for longer bearing life.
2 3/8" Output gearbox shaft	Large output shaft handles shock loads better.
Input driveline: Cat. 6 CV	Holds up to shock loads and harsh mowing conditions. Constant velocity (CV) U-joint allows for 80 degree turns without doing damage to the driveline.
Easy greasable drivelines	Drivelines have access holes for greasing the U-joints and to grease the inner profiles.
4 Plate slip-clutch	Protects drivelines and gearboxes by slipping clutches rather than twisting the driveline when impacts are encountered.
High blade tip speed	Allows clean cutting of material & even distribution. See Specifications for actual FPM.
6" Blade overlap	Eliminates skipping during turns.
Good cutting capacity	Can cut brushy areas with saplings up to 3".
13" Deck height	Handles heavy cutting, which reduces balling-up of cut material under the deck.
Diamond shaped blade holder	Heavy diamond shaped blade holder for protecting the gearbox seal and gearbox output shaft. Can hold up to tough conditions.
Optional dishpan	Dishpan provides extra protection against stumps and other protrusions. Excluding the dishpan eliminates grass/dirt buildup which can cause vibration.
Spindle Nut Protected	Spindle nut and threads extending beyond the nut are guarded to protect against damage from hitting solid objects.
Shredder Blade Kit (Optional)	Ideal for cutting residue into smaller pieces. Replaces standard blade bar/dish configuration.
10 gauge smooth deck top	Reduces accumulation of debris and is easier and faster to clean.
1/4" side skirt	Reduces debris piercing possibilities.
Self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Hinged wing sections	Allows cutter to follow terrain. Ideal for rough ground where hillsides, ditches, and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge gives greater strength to cutter and hinge area.
Wing transport locks	Holds transport wings in the folded-up position in case of hydraulic pressure loss.
Enclosed front to rear dual leveling rods	Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain. Many competitors only use one leveling rod.
5-Bolt hubs	5-Bolt hubs makes the wheel assembly more durable and longer lasting.
Drain holes in wheel rims	Allows water to drain from wheels mounted on folded-up wings. Helps prevent paint deterioration and rusting to the wheel rims.
Spring-cushioned center axle	Protects unit from bumps and ground shock, cushions loads on drawbar.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing the entire axle. Simply remove one bolt to replace damaged spindle.
Rephasing lift cylinders	Allows cutter to be leveled using hydraulic cylinders versus mechanical turnbuckles.
7/8" Leveling rods	Large diameter leveling rods provide superior supporting strength over rough terrain.
LP Performance Hitch option	Great for uneven terrain, reduces drawbar wear. Hitch pivots freely up and down and pivots about the tractor drawbar.
Bar-tite hitch option	Ideal for extreme conditions. Clamps tight to drawbar eliminating drawbar wear.
Roadway light kit option	Allows operator to transport on public roads safer when headlights are turned on and/or when flasher lights are turned on.
Wheel options	Laminated tires: Eliminates flats. Air-filled tires: Give better cushion while transporting. Foam-filled tires: Give better cushion while transporting & can't go flat.
Deck rings (optional)	Keeps blades from damaging the deck.