Features & Benefits

OFM36 Series Offset Flail Mower	
Features	**Benefits**
Multiple cutting widths 78", 90", & 98" (200, 230, & 250 cm)	Wide selection of cutting widths to meet specific applications.
Wide range of tractor horsepower 75 hp to 130 hp (56 kW to 75 kW)	Fits a large array of tractors to meet the needs of consumers, municipalities, and landscapers.
Spring-loaded, belt-tensioning system	Belt tensioner system brings the belt to proper tension by turning a jam nut. Makes maintaining proper belt tension easy, and increases belt life.
High blade cutting capacity	Hammer blade can cut up to 2" (5 cm) brush and small saplings.
Reverse rotor rotation	Brings the cut material up and over the rotor which allows it to be dispersed more evenly. Allows material to be shredded completely.
High blade tip speed	Creates a vacuum effect, provides a clean cut, and slices through saplings with great force.
Five drive belts	Five drive belts distributes the load evenly, which prevents the belts from jumping off the drive when a shock load occurs.
Offsets right	The lateral arm allows the mower to be offset 49" (125 cm) to the right for a closer cut alongside buildings, fences, and roadsides. It also allows the mower to be cutting in a ditch with the tractor traveling along side the ditch.
Flail head can be rotated from horizontal to 65° up or down	Allows mowing along banks and in ditches without putting the tractor on steep inclining or declining surfaces.
Counter-blade (accessory)	Assist shredding material into fine particles.
Replaceable skid shoes	Prevents wear on end panels from ground contact.
Adjustable roller	Provides precision cutting height between 1" and 2 3/4" (25 cm to 70 cm).