

**GB2084 Series**

<b>Bucket</b>	
<b>Features</b>	<b>Benefits</b>
<b>Grade 50 high strength steel shell 3/16" (5 mm) thick</b>	Improved strength & wear versus mild steel
<b>Five 1/2" x 5" (13 mm x 127 mm) bottom wear plates</b>	Extends bucket life
<b>Reinforced bucket corners &amp; side edges</b>	Adds strength & extends bucket life
<b>Drilled cutting edge 5/8" x 6" (16 mm x 152 mm)</b>	Accepts optional bolt on cutting edge
<b>Optional bolt on cutting edge 5/8" x 6" (16 mm x 152 mm)</b>	Reversible and replaceable; extends life of cutting edge
<b>Upper torque tube/lower torque channel</b>	Prevents twisting
<b>Struck capacity .7yd<sup>3</sup> (.5m<sup>3</sup>)</b>	Allows high volume material handling
<b>Universal Quick-Attach mount</b>	Allows grapple to be installed/removed quickly
<b>Grapple</b>	
<b>Features</b>	<b>Benefits</b>
<b>High strength cast grapple tines</b>	Stronger and more aesthetic than welded tines
<b>Tubular steel construction</b>	Resists twisting
<b>Parking stands</b>	Allows grapple to be stored upright when not in use
<b>Spill guard</b>	Helps contain loose material
<b>Dual cylinders 3" @ 3500psi (7.6 cm @ 24MPa)</b>	Large cylinders handle high pressure & loads
<b>Hose kit included</b>	Hoses provided to center tees or valve
<b>Optional lock valve</b>	Prevents hydraulic bleed-off / improves cylinder control
<b>Quick release grapple</b>	Four pin mount system
<b>Large 77" opening</b>	Handles large bales and high volumes of material
<b>Greasable pivot points</b>	Extends grapple life