

# 3P600 COMPACT DRILL

HP REQUIRED  
40 HP Min.

HITCH  
Cat. 1 & 2

COMPACT DRILLS



## Gets into places big drills simply can't.

The 3P600 Min-Till Drill features a highly visible seed level indicator, extremely accurate fluted seed cups, V-bottom inserts on the inside of the seedbox that allow all the seed to be metered, and water tight lids that stay open for filling. This model is ideal for wooded areas.

The rugged 00 Series openers provide accurate and consistent seed placement. Openers have 7" of stagger between the opening and press wheels to allow residue to easily flow through the unit. Inside the opener our full length seed tube gently guides the seed all the way to the bottom of the trench and a seed flap makes sure the seed stays in the trench. The trailing press wheels maintain proper opener depth, close the seed trench, and firm the seed into the soil. T-handles quickly adjust the press wheels and allow for small incremental changes in planting depth.



### 00 SERIES

Choice of 2x13 Single Press Wheels or 3x13 Center Rib Press Wheels.

	3P600
Horsepower	40 HP min.
Hitch	3-Pt., Cat. 1 & 2
Primary Design	Min-Till
Row Spacings	6", 7-1/2"
Number of Openers	11 - 6" Spacing, 9 - 7-1/2" Spacing
Weight - lbs (kg)	1,500 (680)
Working Width	6'
Width	6'
Transport Length	Varies by Tractor
Transport Clearance	Varies by Tractor
Transport Height	Varies by Tractor
Opener Series	00 Series
Opener Travel	6.5"
Opener Depth Range	0 - 3-1/2"
Opener Down Pressure - lbs	90-180
Main Box Capacity	12 bu.
Small Seed Box	1.44 bu.
Color	