

# APS15 SERIES ALL-PURPOSE SEEDERS

HP REQUIRED  
25-130 HP

HITCH  
Cat. 1 & 2

SEEDERS



## The seeder that does it all.

The APS15 is at home in freshly prepared soil or overseeding existing turf. The front spike rollers break up the soil crust or penetrate the thatch to disturb the right amount of soil. The seed is dropped, protected from the wind by a shield, allowing it to drop to the ground where it is gently pressed into the soil by the notched or spiked rear roller. The initial seed-to-soil contact is essential to achieving a high germination rate.

The All-Purpose Seeder is ground driven with no driveline and related drivetrain components to maintain. By adjusting the front two rollers, you can control how aggressive you want to be in the area you are seeding or overseeding.

### The many uses for the APS:

- Bare dirt seeding
- Turf overseeding
- Wildlife Conservation Seeding



Choose between a rear spiked roller or a 12" cast packer wheel roller.



Optional small seeds box.

	APS1548	APS1560	APS1572	APS1586
<b>Horsepower</b>	25-130 HP			
<b>Hitch</b>	Cat. 1			Cat. 1 & 2
<b>Working Width (cm)</b>	50" (127)	60" (152)	72" (183)	86" (218)
<b>Overall Width</b>	60"	72"	81"	98"
<b>Overall Length</b>	49"	51"	52"	55-1/2"
<b>Overall Height</b>	42-1/2"			
<b>Weight - lb (kg)</b>	547 (248)	702 (318)	836 (379)	1,070 (485)
<b>Seedbox Capacity</b>	4	5	6	7.2 Bushel
<b>Output Range</b>	Varies By Seed Variety; Consult Manual			
<b>Front Roller - 2</b>	8" Diameter, 1" Spindles w/Greaseable Ball Bearings			
<b>Rear Roller</b>	8" Diameter w/Studs or 12" Cast Packer Wheels			
<b>Chain</b>	#40 with Spring Loaded Idler			
<b>Seed Cups</b>	7	8	10	12
<b>Front Roller Angling</b>	Up to 20°			
<b>Roller Studs</b>	1/2" to 2" Heat Treated Steel, Replaceable			
<b>Transport Lights</b>	Standard			
<b>Color</b>				

\*60" and 86" models with rear cast packer wheels



\*See dealer for complete warranty information.