

CB25/35 SERIES COMBINATION BUCKETS

Available for: SSV65 | SSV75 | SVL65 | SVL75 | SVL97

MATERIAL HANDLING



KEY FEATURES

- 4-in-1 Design: bucket, scraper, grapple, and dozer
- Dual cutting edge on jaw
- Bolt-on edge on back blade
- Cylinder protection
- Struck cap. 10–17 cu. ft.; Heaped cap. 15–24 cu. ft.

Dirt and concrete contractors, landscapers, and farmers get the versatility of a grapple, dozer blade, bucket, and back scraper, all in one tool with the CB25 & CB35.



Various sizes of objects can be held securely in the serrated interlocking grapple teeth.



Four functions in one unique attachment allow you to use it as a bucket, scraper, grapple and dozer.

		CB2568	CB2574	CB2580			
Hitch Type		Universal Quick-Attach					
Weights - lbs (kb)	Without Teeth	1,006 (456)	1,054 (478)	1,146 (520)			
	With Teeth	963 (436)	1,018 (462)	1,089 (494)			
Overall Width (m)		71" (1.8)	77" (1.96)	83" (2.1)			
Clamshell Opening (cm)		33" (83.8)					
Bucket Capacity ft³ (m³)	With & Without Spill Guard	With	W/O	With	W/O	With	W/O
	Struck Full Heaped Full	13.45 (.38)	10.09 (.28)	14.65 (.41)	10.99 (.31)	15.86 (.44)	11.89 (.33)
		18.45 (.52)	15.20 (.43)	20.14 (.57)	16.61 (.47)	21.83 (.61)	18.01 (.51)
Hydraulic Cylinder Pins (cm)		1" (2.5) Diameter greaseable rod pivot pins					
Jaw Pivot Pins (cm)		1-1/4" (3.2) Diameter greaseable pivot pins					
Hydraulic Cylinder (cm)		2.5" x 8" x 1-1/4" (6.4x20.3x3.2) Rod					
Max. Hydraulic Pressure (MPa)		3500 psi (24.1)					

		CB3574	CB3580		CB3584		
Hitch Type		Universal Quick-Attach					
Weights lbs (kg)	Without Teeth	1,095 (497)		1,165 (528)		1,225 (556)	
	With Teeth	1,040 (472)		1,105 (502)		1,160 (526)	
Overall Width (m)		76-1/4" (1.94)		82-1/4" (2.09)		86-1/4" (2.19)	
Clamshell Opening (cm)		33" (83.8)					
Bucket Capacity ft³ (m³)	With & Without Spill Guard	With	W/O	With	W/O	With	W/O
	Struck Full Heaped Full	14.75 (.42)	9.75 (.28)	16 (.45)	10.5 (.3)	16.75 (.47)	11 (.31)
		20.5 (.58)	14.5 (.41)	22.33 (.63)	15.75 (.45)	23.5 (.67)	16.5 (.47)
Hydraulic Cylinder Pins (cm)		1-1/4" (3.2) Diameter greaseable rod pivot pins					
Jaw Pivot Pins (cm)		1-1/4" (3.2) Diameter greaseable pivot pins					
Hydraulic Cylinder (cm)		2-1/2" x 8" x 1-1/2" (6.4x20.3x3.8) Rod					
Max. Hydraulic Pressure (MPa)		3550 psi (24.5)					