

CTR10 COMPACT TRENCHERS



new

AVAILABLE FOR: SCL1000

- 30", 36", 48" Trenching depths
- 2 Motors; high speed or high torque
- Positive manual chain tensioner
- Heavy-duty hitch plate
- Chain widths on 30"/36" units: 4", 6", 8" & 10"
- Chain widths on 48" unit: 4" & 6"
- 3 Chain styles

Designed for efficient digging of trenches and ideal for irrigation or utility contractors, or as a rental tool.



	CTR1030	CTR1036	CTR1048
Operating Weight (w/4" 2 pitch cup chain & optional crumber)	484 lbs (220)	516 lbs (234)	559 lbs (254)
Overall Length (cm)	62" (157)	72" (183)	85" (216)
Digging Depth at 60°	30" (76)	36" (91)	48" (123)
Overall Width (cm)	32.4" (82)		
Overall Height (cm)	33" (84)		
Spoil Auger (cm)	12.25" (31) - Removable		
Trenching Widths Available	4", 6", 8", 10"		4", 6"
Motor Options	High speed or high torque		
Hydraulic Motor Flow	20 gpm max. continuous		
Crumber	Floating - optional equipment		
Depth Indicator	Standard - visible from operator's platform		
Roller Guide Bearing at Boom Head	Sealed, ball bearings with triple lip seals & metal shroud covers		
Drive Bearings	Sealed, double row ball bearings with heavy duty seals		
Chain Speed @15gpm	638 fpm (high torque) / 1105 fpm (high speed)		
Chain Tightener	Threaded		
Chain Options	Cup teeth on 2 or 4 pitch, or 2 pitch scorpion w/cup teeth		
Trencher Chain	1.654" Pitch, 34,000 lb tensile strength		
Trencher Chain Side Links	Anti-flex		
Cup Teeth	Hardened with hard facing		



Chain options range from 4" to 10" widths and are available in 3 styles: 2-cup, 4-cup, or scorpion and cup chain.



The trench is cleared with a 12" spoil auger and smoothed with an optional crumber tool.