FDR36 SERIES GROOMING MOWER

30-70 HP | Cat. 1 Hitch



Call it "Contractor-duty"

Our FDR3690 Grooming Mower is built for commercial use by mowing contractors. Contractors will appreciate the ease of maintenance and the 6 free-swinging mediumlift blades that provide a uniform cut in heavy turf grasses. The tapered deck design allows operators to get close to obstacles while the rear discharge directs debris toward the ground, allowing for even distribution of clippings.



The FDR36 frame-over-deck design is engineered for maximum airflow, featuring a roll-formed 1/4" leading edge, 6 free-swinging blades and a tapered and sloped rear deflector.





Rear discharge distributes an even layer of grass directly behind the mower, keeping grass from blowing in unwanted areas.



Main drive cast iron pulley offers superior strength and belt slippage control.



Ca

Clevis type lower hitch points allow for easy hook-up. Simply remove pins and back into clevises.

	FDR3690
Horsepower	30-70 HP
Hitch	Cat. 1
Working Width	90" (229)
Overall Width (cm)	92" (234)
Weight - Ib (kg)	930 (422) (w/o Front Roller)
Mowing Height	1" - 6-1/2" in 1/4" Increments w/Plated Spacers
Discharge	Rear
Lower Hitch	Floating Clevis w/Plated Pins
Top Link	Floating Clevis
eck Material Thickness	3/16"
Blades 6 ea.	Free Swinging, 1/4" x 2-1/2" x 14" Hardened, Medium Lift (2 per Blade Spindle)
Blade Overlap	2"
Blade Tip Speed	16,500 fpm
Blade Spindles	1-3/8" Stressproof [®] Shaft
Deck Spindle Housings	Cast Iron Greasable Hubs
Drive Train	540 rpm Double V Powerband Belt
Belt Take-up	Spring Loader Idler
Gearbox	540 rpm, Cast Iron Housing with Beveled Gears
astered Gauge Wheels	5" x 13" Semi-Solid Tire with Bearings
astered Wheel Spindle	1-1/4" Diameter with Greasable Bushing
Driveline	Heavy-Duty Cat. 4 w/Quick Coupler
Front Roller	Optional
Colors	
QUICKHITCH	

