

FM25 SERIES FLAIL MOWERS

HP REQUIRED
30-80 HP


HITCH
Cat. 1 & 2



MOWERS

Sturdy and compact.

Land Pride's FM25 Series Flail Mowers are built for use in vineyards, orchards, and recreational areas and will fit a wide variety of tractors. The spring-loaded belt-tensioning system makes it easy to tension belts for longer life. Cutting height is variable from 0" to 6". The rear access door and quick-change D-ring system (Duckfoot knives only) simplifies blade changes.




Optional brush rake teeth keep material in to pulverize it.



The dynamically balanced rotor is driven by a three section PowerBand® belt and mounted on spherical roller bearings.



Unique spring-loaded belt-tensioning system brings belt to proper tension by turning a nut. (N/A on 48")



Three different blade options make quick work of grass, grapevine shoots, saplings, and tree prunings.

	FM2548	FM2560	FM2572	FM2584
Horsepower	30-80 HP			
Hitch	Cat. 1		Cat. 1 & 2	
Weight - lb (kg)	780 (354)	929 (421)	1,040 (472)	1,168 (530)
Working Width (cm)	48" (122)	60" (152)	72" (183)	84" (213)
Overall Width	60"	72"	84"	96"
Drive Cover Height	33"			
Rotor RPM	2,450			
Gearbox Rating	80 HP	80 HP	80 HP	80 HP
Driveline	Cat. 4			
Offset Hitch	Center, 8" Right		Center, 10" Right	
Blade Tip Speed	12,046 fpm			
Knives Attachment	D-Ring for Light Blades, C-Clamp for Heavy Blades			
Duckfoot Blades (Qty)	20	24	28	32
Heavy Y Blades (Qty)	24	32	40	48
Hammer Blades (Qty)	12	16	20	24
Rotor Bearings	Spherical Roller Bearing			
Brush Rakes (optional)	6	8	9	11
Rotor Diameter	5" with Reinforcing Bars			
Rotor Rotation	Reverse			
Cutting Height	0"-6"			
Cutting Capacity	Duckfoot Knives: 1" Heavy-Duty Y Knives: 1.5" Hammer Knives: 2"			
Rear Roller Diameter	5.56"			
Hood/Deck Thickness	10 Gauge			
Color				

PowerBand® is a Registered Trademark of the Gates Corporation



*See dealer for complete warranty information.