

MR15/HR25 SERIES BOX SCRAPERS

HP REQUIRED
20-60 HP

HITCH
Cat. 1

DIRTWORKING




Choose from manual or hydraulic retractable box scrapers.

The easy and convenient retractability of the scarifier shanks on the MR1572 and HR2572 makes them highly productive and ideal for ripping, leveling, finish grading, and backfilling applications at commercial feedlots, outdoor arenas, building sites, and maintenance operations on farm and ranch lanes, gravel, roadways, or constructions sites.

The roll-formed moldboard keeps materials flowing which puts less drag on the Box Scraper, resulting in lower HP requirements and faster working conditions. Shanks on the MR15 are kept in the up or down position with a positive locking system, keeping the scarifier bar from bouncing in transport and tight during field use.

- Self locking down position
- Hydraulic raising and lowering of shanks on HR25
- 3 Position shank with replaceable tip
- Rigid backfill blade



The hydraulic retractable ripping shanks on the HR25, in combination with the 21" double-thick moldboard design, make these units highly productive for construction projects.

	MR1572	HR2572
Horsepower	2WD: 20-50 HP 4WD: 25-40 HP	30-60 HP
Hitch	Cat. 1	
Working Width (cm)	72" (183)	
Height of Moldboard	18-1/2"	20-1/2"
Depth of Side Panels	27-1/2"	34"
Side Plate Material	3/8"	
Weight - lb (kg)	615 (279)	851 (386)
Number of Shanks	7	
Cutting Edges	Two 1/2" x 6" High Carbon Heat Treated Blades, Reversible & Replaceable	
Colors		