

HRS30 SERIES HYDRAULIC RESERVOIR SYSTEMS


 HP REQUIRED
 52 HP Min.


 HITCH
 Cat. 1 & 2

SNOW TOOLS



Add hydraulic power with ease.

The HRS is a self contained power pack to run log splitters, chippers, front-mounted snowblowers and more. Easily hook to the 3-Point hitch on your tractor, hook the driveline to the tractor's PTO shaft, and you have a convenient supply of hydraulic power.

Optional Valve Selections

- **No Valve** - Use PTO to turn hydraulics on and off
- **Manual Valve** - Use remote valve to turn hydraulics on and off
- **Solenoid Valve** - Use electronic control to turn hydraulics on and off



35 Gallon self contained reservoir with 10 micron filter provides more than ample amounts of clean and cool hydraulic fluid for even the most demanding applications.

The oil cooler on the Hydraulic Reservoir System cools the oil when necessary and is included with the hand valve and solenoid valve options. It is optional with the no valve option.



	HRS3025
Horsepower	52 Min.
Hitch	Cat. 1 & 2
Pump Capacity	Approx. 25 GPM @ 540 RPM
PTO Input Speed	540 RPM
Hydraulic Fluid Type	Mobil Fluid 424
Overload Protection	Hydraulic Relief Valve
Reservoir Capacity & Filter Type	35 Gallons, Conventional 10 Micron Filter
Overload Protection	3,000 PSI Hydraulic Relief Valve
Driveline	Category 3
Pressure & Return Hose Lengths	24 Feet Each
Case Drain Port	3/4" - 16 UNF
Hydraulic Cooler	Optional
Color	