

RB26/37 SERIES REAR BLADES

HP REQUIRED
25-80 HP


HITCH
Cat. 1 & 2

DIRTWORKING



Everyday blades; dirt, snow, farm, landscape – About as versatile as it gets!

The Land Pride RB26 and RB37 Series Rear Blades offer 3-way positioning (blade angle, blade tilt, and blade offset) and are an excellent choice for leveling, grading, or backfilling. They excel in snow removal in either the pulling or push blade mode. Their offset and tilt capability make them an excellent choice for construction and maintenance of drainage ditches, waterways, soil contours, and for maintaining silage pit operations. Optional hydraulic angling kits are available for both models.



A parking stand allows the front of the hitch to be off the ground when storing, and offers easier hook-up.



Optional side plates hold material in to be moved, while optional skid shoes keep the cutting edge off the ground to protect from hitting low obstructions.

	RB2672	RB2684	RB2696	RB3772	RB3784	RB3796
Horsepower	25-60 HP			35-80 HP		
Hitch	Cat. 1			Cat. 1 & 2 Combination		
Working Width (cm)	72" (183)	84" (213)	96" (244)	72" (183)	84" (213)	96" (244)
Weight - lb (kg)	369 (167)	396 (180)	425 (193)	595 (270)	630 (286)	665 (302)
Angling	7 Fwd. Up to 45°; 3 Rev. Up to 60°			7 Fwd. Up to 45°; 3 Rev. Up to 30°		
Tilt	5 Positions; Up to 15° Left or Right, 30° Total			7 Positions; Up to 22.5° Left or Right, 45° Total		
Offset	12"			26" Left or Right		
Moldboard Height	17-1/2"			17"		
Moldboard Thickness	5/16"			5/16"		
Kingpin	3-1/2" Tube			2-1/2" Solid Shaft		
Cutting Edge	1/2" x 6", Reversible & Replaceable; Heat Treated			1/2" x 6", Reversible & Replaceable; Heat Treated		
Options	Side Plates, Skid Shoes, Hydraulic Angling			Side Plates, Skid Shoes Hydraulic Angling		
Colors						