

RBT45/55 SERIES REAR BLADES

HP REQUIRED
70-180 HP

HITCH
Cat. 2 & 3

DIRTWORKING



Built tough...where it really counts.

Land Pride's RBT45 and RBT55 Series 3-Way Hydraulic Rear Blades are ideal for landscaping, construction, snow removal, feedlot cleaning, and all-around farm use. Make changes on the go with hydraulics at all three positions and use your time more efficiently. Available options include single or double hydraulic gauge wheels, side plates for holding dirt in, and skid shoes for blade protection.



Shown with optional end plates.



Pivot weldment features a 1" thick plate steel turntable, 3/4" thick tilt pivot bushing and a 4" solid kingpin.



Optional cushion valve on the RBT45 protects cylinders and blade components during extreme impacts.



Optional single or dual gauge wheels add accuracy and simplify grading operations.

| | RBT4596 | RBT45108 | RBT55120 |
|---------------------------------|--|-------------------|---|
| Horsepower | 70-125 HP | | 90-180 HP |
| Hitch | Cat. 2 & 3 | | Cat. 2 & 3 |
| Working Width (cm) | 96" (244) | 108" (274) | 120" (304) |
| Weight - lb (kg) | 1,130 (513) | 1,166 (529) | 1,753 (795) |
| Maximum G.V.W. - lb (kg) | 9,500 (4309) | | 15,000 (6818) |
| Blade Angle | Fwd & Rev Up to 45° | | Fwd & Rev Up to 45° |
| Angle Cylinder | 4" x 16" | 4-1/2" x 16" x 2" | |
| Tilt | Up to 15° | | Up to 30° |
| Tilt Cylinder | 3" x 6" x 1-1/4" | 3" x 8" x 1-1/4" | |
| Swing Offset | Up to 35" Left and Right | | 33" |
| Offset Cylinder | 4" x 16" | 4-1/2" x 16" x 2" | |
| Moldboard Height | 19" | | 19" |
| Moldboard Thickness | 5/16" with 1/4" Boxed Reinforcement | | 5/16" with 1/4" Boxed Reinforcement |
| Cutting Edge | 1/2" x 6", Reversible & Replaceable; Heat Treated | | 1/2" x 6", Reversible & Replaceable; Heat Treated |
| Options | Skid Shoes, End Plates, Single or Dual Gauge Wheel, Cushion Valve, Double Selector Valve | | Skid Shoes, End Plates, Hardened Wear Plates, Hydraulic Single Gauge Wheel, Hydraulic Dual Gauge Wheel, Double Selector Valve |
| Colors | | | |

