RC36 SERIES OFFSET/FOLDING

ROTARY CUTTERS











Holds up to tough conditions.

Land Pride's RC3620 is the ideal Rotary Cutter for grassy fields, pastures, waterways, buffer strips, and set-aside acres and handles saplings up to 2" in diameter. With tip speeds of 16,000 to 16,500, gearboxes rated at 250 HP and 150 HP, 1-3/4" input shafts, 2" output shafts,

and optional CV drivelines, this unit will make quick and efficient work of the largest jobs.

> Also available as a 14' offset model: RC3614.



10 Gauge stump jumper is backed with a 1" x 4-1/2" thick blade mounting bar to protect the gearbox seal and output shaft.

> Rephasing lift cylinders allow cutter to be leveled using hydraulic cylinders versus mechanical turnbuckles.



Land Pride



1	Horsepower		70-160 HP	
	Hitch		Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite	
10	Working Width (cm)		14' (426)	20' (607)
		Overall Width	15'	20' 10"
1	Min. Transport Width		8' 9"	9' 11"
	Overall Length		17' 6" with Laminated Tires	
W. Car	Machine \	Weight - Ib (kg)	5,990 (2717)	6,680 (3,030)
A RES	(Cutting Height	2" - 12"	
1000	Cutting Capacity		2" Diameter	
	Tongue Weight - Ib		2,220	1,750
100	Max. Turning Angle		80° with CV	
1	Deck Height		13"	
	Deck Thickness		10 Gauge	
	Suspension		Spring on Center Deck	
	Deck Rings		Optional	
	Side Thickness		1/4"	
	Chain Guards Front & Rear Skid Shoes Blades		Single - Standard Double - Optional	
			Wings & Center, Replaceable	
			1/2" x 4" High Lift	
	Blade Bolt		Keyed with Hardened Flatwasher & Lock Nut	
4	Blade Tip Speed (Feet per minute)	540 Center	16,000 fpm	
		Wings	16,000 fpm	
		1000 Center	16,500 fpm	
		Wings	16,500 fpm	
		Blade Overlap	6"	
75		Dishpan	10 Gauge Round, Dish Shaped w/ 1" x 4-1/2" Blade Bar	
	Hydraulics	Wings	3" x 12" Cylinder	
		Center	2-3/4" x 8" RH Wing-3" x 8", LH Wing-3-1/4" x 8"	
	Ge	earbox Rating^	540 RPM or 1000 RPM: 250 HP Divider, 150 HP Center & Wings	
	Gearbox Output Shaft Gearbox Input Shaft Input Driveline Connecting Drivelines		2"	
			1-3/4" 20 Spline	
			Cat. 6 CV	
			Cat. 4 Slip Clutch	
	Tires RC3614: 5 or 6 RC3620: 6 or 8		21" Laminated, 29" Used Aircraft, or 27" Foam-Filled	



Standard

Transport Lights

Colors