

RC3712 ROTARY CUTTERS

12' FLEX-WING: 50-160 HP | Pull-Type




RC3712 HEAVY-DUTY		
Horsepower	50-160 HP	
Hitch	Pull-Type; Standard Swivel Clevis, LP Performance Self-Leveling, Ball, Pintle, or Bar-Tite Hitch	
Working Width (cm)	12' (366)	
Overall Width	12'10"	
Min. Transport Width	9' 4"	
Overall Length	15'3"	
Machine Weight - lb (kg)	3,730 (6,192)	
Cutting Height	1-1/2" - 14"	
Cutting Capacity	3" Diameter	
Tongue Weight - lb	1,240	
Max. Turning Angle	80° with CV	
Deck Height	11"	
Deck Thickness	10 Gauge	
Suspension	Spring Cushioned Center Axle	
Deck Rings	N/A	
Side Panel Thickness	1/4"	
Chain Guards Front & Rear	Single - Standard Double - Optional	
Skid Shoes	Wings & Center, Replaceable, Beveled	
Blades	1/2" x 4" Uplift	
Blade Bolt	Keyed with Hardened Flatwasher & Lock Nut	
Blade Tip Speed (Feet per minute)	540 Center	15,514 fpm
	Wings	15,474 fpm
	1000 Center	15,700 fpm
	Wings	15,707 fpm
Blade Overlap	6"	
Dishpan	10 Gauge Round, Dish Shaped w/ 1" x 4-1/2" Blade Bar	
Hydraulics	Wings	2-1/2" x 12"
	Center	3" x 8"
Gearbox Rating^	540 or 1000 RPM: 160 HP Divider; 130 HP Center & Wings	
Gearbox Output Shaft	2"	
Gearbox Input Shaft	1-3/4" 20 Spline	
Input Driveline	Cat. 6 CV	
Connecting Drivelines	Cat. 4 Slip Clutch	
Tires	21" or 26" Laminated, 25.5" Aircraft, or 24" Foam-Filled	
Transport Lights	Standard	
Color Options		

Tough enough.

The RC3712 Flex-Wing Rotary Cutter expands on the popularity of our RC2512 by offering a heavy duty 12-foot cutter. It features a 3" cutting capacity with a cut height of 1.25" to 14". The cutter is available for 540 or 1000 RPM tractors, with 4 or 6 tires in 3 sizes, and 5 hitch options. Standard equipment includes transportation lights, wing transport locks and replaceable skid shoes.



Low hitch weight on tractor drawbar is ideal for smaller horsepower tractors. Narrow A-frame hitch allows for tighter turns.



Greasable hinged wing sections have 1" solid hinge rods and allow the cutter to follow rough ground, alleviating uneven cutting.



Beveled skid shoes on wings reduces gouging of the ground when turning.



3/16" Thick stump jumper protects the gearbox output shaft.