RC4715 ROTARY CUTTERS

15' FOLDING: 55-250 HP | Pull-Type

CUTTING CAPACITY 4"

Make pasture and roadside maintenance a simple and efficient task.

The RC4715 is a heavy-duty folding rotary cutter with a 4" cutting capacity and 15' cutting width designed to make pasture and roadside maintenance a simple and efficient task. The unit comes with ease of maintenance features that you've come to expect from Land Pride like greaseless pivot points, endcap grease zerks, easy-off shields and a patented sliding guard over the splitter gearbox, making maintenance easy to perform. There are multiple axle options, including Land Pride's parallel pivot that gives you unmatched ground contact for improved holding power on hills and inclines, as well as 5 tire options in 6 or 8 tire configurations.

Land Pride's patent pending parallel pivot axle gives you unmatched ground contact for improved holding power on hills and inclines.

7 YEAR LIMITED GEARBOX WARRANTY*

Spring cushioned axles improve ride and are available options on both center and wing axles.

Easy-off shields and a patented sliding guard over the splitter gearbox make maintenance easy to perform.

Forged diamond blade bar provides strength where it's needed most.

		RC4715 HEAVY-DUTY
Horsepower		55-250 HP
Hitch		Pull-Type; Standard Swivel Clevis, LP Performance Self-Leveling, Ball, Pintle, or Bar-Tite Hitch
Working Width (cm)		15' (457)
Overall Width		15' 10"
Min. Transport Width		7'3"
Overall Length		16'3"
Machine Weight - lb (kg)		5,000 (2,268)
Cutting Height		1-1/2" - 16" **
Cutting Capacity		4" Diameter
Tongue Weight - lb		1,860
Max. Turning Angle		80˚ with CV
Deck Height		12"
Deck Thickness		10 Gauge
Suspension		Spring Cushioned Center Axle
Deck Rings		Optional
Side Panel Thickness		1/4"
Chain Guards Front & Rear		Single - Standard Double - Optional
Skid Shoes		Wings and Center, Beplaceable, Beveled
Blades		1/2" x 4" Uplift
Blade Bolt		Keyed with Hardened Flatwasher & Lock Nut
Blade Tip Speed (Feet per minute)	540 Center	16,300 fpm
	Wings	16,300 fpm
	1000 Center	16,300 fpm
	Wings	16,000 fpm
Blade Overlap		6"
Dishpan		Forged Diamond Blade Bar; Optional 3/16" Round Dishpan
Hydraulics	Wings	2-1/2" x 12"
	Center	3" x 8"
Gearbox Rating^		540 or 1000 RPM: 250 HP Divider, 210 HP Center & Wings
Gearbox Output Shaft		2-3/8"
Gearbox Input Shaft		1-3/4" 20 Spline
Input Driveline		Cat. 6 CV
Connecting Drivelines		Cat. 4 or Cat. 5 Slip Clutch
Tires		21" or 26" Laminated, 29" Used Aircraft 24" Foam-Filled
Transport Lights		Standard
Color Options		

*See dealer for complete warranty information. **Varies by tire option
^Based on field performance.

Land Pride
landpride.com