

RCF30 SERIES DUAL SPINDLE ROTARY CUTTERS

HP REQUIRED
40-110 HP

CUTTING CAPACITY
2-1/2"

HITCH
Cat. 1, 2 & 3



CUTTERS

Performance in a Medium-Duty Cutter.

The RCF30 Series is the perfect medium-duty cutter for pastures and roadside applications. Available in 3-Point, semi-mount or pull-type, the RCF30 features a 2-1/2" cutting capacity and 1/4" side skirts. Plus, every RCF30 comes with the rugged dependability that Land Pride Rotary Cutters are known for.



3-Point with Dual Beam Axle

	RCF3096	RCF3010
Horsepower	3-Pt: 50-110 HP Semi & Pull: 40-110 HP	3-Pt: 60-110 HP Semi & Pull: 50-110 HP
Hitch	Cat. 1 & 2 QH	Cat. 2 & 3 QH
Working Width (cm)	8' (244)	10' (305)
Overall Width	8'7"	10'6-1/2"
Overall Length (3-Pt w/Twin Beam Axle)	102"	122"
Weight - lb (kg) (3-Pt w/Twin Beam Axle)	1,587 (720)	2,004 (909)
Deck Thickness	10 Gauge	
Side Skirt Thickness	1/4"	
Gearbox Rating[^]	Outboard: 130 HP, Center 210 HP	
Gearbox	540 RPM	540 RPM or 1,000 RPM
Cutting Height	2" - 12"	
Cutting Capacity	2-1/2" Diameter	
Shielding	Front: Rubber, Chain or Double Chain Rear: Rubber, Chain or Double Chain	
Skids	Replaceable	
Deck Height	11-1/4"	11-1/2"
Blades	1/2" x 4" Heat Treated Alloy Steel Free Swinging Blades	
Blade Tip Speed	16,360 fpm	540: 17,100 fpm; 1000: 17,300 fpm
Dishpan	3/16" Round, Dish Shaped	
Driveline	3-Point & Semi-Mount: Cat. 4 Pull-type: Cat. 4 Equal Angle or CV	
Driveline Protection	Slip-Clutch and Impact Absorbing Cross Shafts to Outer Gearboxes	
Tailwheels	3-Point: 15" or 21" Laminated Pull-Type: 21" Laminated, 24.5" Foam Filled, or 29" Aircraft Tires Semi-Mount: 15" or 21" Laminated	
Colors		



Dual heavy-duty standard stump jumpers aide in sliding over obstructions which helps protect the gearbox output shaft.

5 YEAR LIMITED GEARBOX WARRANTY*

Splined rubber flex-couplers between the center and outboard gearboxes protect the driveline and gearboxes from shock loads.



*See dealer for complete warranty information. ^Based on field performance.

