

Achieve long lasting results with top quality components.

The auger pulls the snow inward as the auger paddles direct it into the high speed impeller. Snow is thrown out of the adjustable chute so you can direct it right where you want it. Because the Snow Blower is making two points of contact with the snow, it can break up hard compacted snow and cover a wider clearing path.

- Hardened Cutting Edge
- Shear Bolt Driveline
- Heavy Duty Chute
- Choice of Skid Shoes
- Telescoping 3-Point



	SB1051	SB1064	SB1574
Horsepower	18-32 HP	18-59 HP	30-59 HP
Telescoping Hitch	Cat. 1, Quick-Hitch Adaptable		Cat. 1, Quick-Hitch Adaptable
Working Width (cm)	51" (130)	64" (163)	74" (188)
Weight - lb (kg)	390 (177)	501 (227)	545 (247)
Main Housing Material	12 Gauge		12 Gauge
Side Plate Material	3/16"		3/16"
Optional Cutting Edge	Bolt-on, Reversible & Replaceable Hardened Steel		Bolt-on, Reversible & Replaceable Hardened Steel
Optional Skid Shoes (Choice of)	Outer: Bolt-on, Adjustable & Replaceable Wear Plate: Bolt-on, Hardened, Replaceable and Reversible Button Style: Adjustable & Replaceable		
Impeller	20" Diameter, 4 Blades		24" Diameter, 4 Blades
Impeller Housing Depth	6"		8"
Auger	1 - 14" Diameter, 3/8" x 2-1/2" Flighting		1 - 16" Diameter, 3/8" x 2-1/2" Flighting
Auger Paddles	2	4	4
Drive Chain	#60 Heavy		#60 Heavy
Chute Opening at Base	8"		10"
Chute Rotation	Sprocket Type; Manual, Electric or Hydraulic		Sprocket Type; Manual, Electric or Hydraulic
Chute Deflector Operation	Manual, Electric or Hydraulic		Manual, Electric or Hydraulic
Driveshaft Shear Bolt	Grade 5 - 1/4 x 20		Grade 5 - 1/4 x 20
PTO Driveline	Cat. 2, Shear Bolt		Cat. 3 Heavy, Shear Bolt

Color Options:



See page 109 for photos of Snow Blower options.