

SSG20 SERIES STUMP GRINDER

Available for: SCL1000 | U27 | U35 | U48 | U55 | KX030 | KX033 | KX040 | KX057

MATERIAL HANDLING

SSV65 | SSV75^{Std Flow only} | SVL75^{Std Flow only}



KEY FEATURES

- 8-21 gpm
- Fits Compact Loaders, Skid Steers, Compact Excavators
- Optional mounts
- 24" Cutting wheel
- Direct drive
- 15 Wearsharp® teeth

Versatility is the name of the game for the SSG20 Stump Grinder. With a variety of mounts and hose options available, the SSG20 fits compact loaders, skid steers, and compact excavators.



Skid steer mount

Excavator mount

SCL mount

SSG2024	
Hitch Type	Universal Quick-Attach Excavator mount & bolt-on options Compact Utility Loader CII Mount
Overall Width (cm)	40" (102)
Overall Height (cm)	32" (81)
Weight - lbs (kg)	279 (127)
Mount Weight - lbs (kg)	Skid Steer mount: 168 (76) Excavator mount: 86 (39) CII mount: 83 (38)
Hydraulic Requirements (Lpm)	8 to 21 gpm (30.3-79)
Cutting Wheel Diameter (cm)	21" (53)
Cutting Wheel Thickness (mm)	0.625" (16)
Cut Diameter (cm)	24" (61)
Max. Cutting Depth Below Ground (cm)	10" (25)
Cutting Components	(15) Wearsharp® carbide teeth (12) Bent tooth holders (3) Straight tooth holders
Cutting Wheel Rotation	Clockwise (when viewed from attachment's extension spring side)
Cutting Direction	Forward cutting only
Max. Pressure Rating (mPa)	3500 psi (24.1)
Hydraulic Couplers	Quick connect couplers (flat-face)