

STB05 SERIES TRIP BLADES

HP REQUIRED
17-30 HP

HITCH
Universal
Quick-Attach

SNOW TOOLS



Ideal for moving snow or dirt.

Land Pride's STB05 Series Trip Blades are available in 54" and 60" widths and are intended for use on Kubota BX and B01 Tractors with universal quick attach hitch. The STB05 has a lower profile 17" moldboard for smaller tractors and is lighter than our 10 Series making it more appealing for sub-compact tractor owners.

The 12 gauge curved moldboard features dual springs that allow the blade to trip forward when contacting stationary objects. The blade is angled using a Land Pride 3rd Function Valve and has a 24° angle left to right. Optional steel or poly cutting edges are reversible and replaceable. The STB05 is ideal for small contractors that move snow or light aggregate or dirt.



| | STB0554 | STB0560 |
|---|--|-----------|
| Horsepower Range | 17-30 HP | |
| Hitch/Mount | Universal Quick-Attach | |
| Widths | 54" (137) | 60" (152) |
| Weight* - lbs (kg) | 284 (174) | 316 (143) |
| Moldboard Height | 17" Curved Blade | |
| Moldboard Material | 12 Gauge, Formed | |
| Moldboard Spring Trip | 2 Spring Protection | |
| Moldboard Trip | Can be Locked for Light Grading | |
| Blade Widths (cm) | 54" (137) | 60" (152) |
| Skid Shoes Button Style Standard | AR400 Material | |
| Angling | 24° Left or Right | |
| Optional Hydraulic Cylinder(s) | Single | |
| Manual Angle Positions | 0°, 12°, 24° Left/Right | |
| Adjustable Spring Tension | Standard | |
| Trip Force @ Blade | 250-400 lbs | |
| Carrier Lift Capacity - lbs (kg) | Less than 1,000 (454) | |
| Carrier Max. Operating Weight - lbs (kg) | Less than 2,000 (907) | |
| Max. Hydraulic Pressure Rating | 3,000 PSI | |
| Replaceable Wear Edge | Reversible: 3/8" x 6" 1080 Steel or 1/2" x 6" Poly | |
| Marker Kit | Standard | |
| Top Rubber Deflector | Optional | |
| Color | ■ | |