

STP15/25 TREE/POST PULLERS




STP15: AVAILABLE FOR: SSV65
STP25: AVAILABLE FOR: SSV65 / SSV75 / SVL65-2 / SVL75-2 / SVL95-2

- 10" Jaw opening
- Laser cut saw tooth design
- Interlocking teeth on the jaws
- 3" x 3-1/2" Square tubing frame

The STP15 is great for property owners and small landscapers for removing shrubs, saplings, and small trees; pulling them from the ground, roots and all. The STP25 is heavier duty and ideal for farmers/ranchers, fence builders, and landscapers for removing trees up to 10" in diameter.



Fittings and hydraulic hoses are protected at the hydraulic cylinder with a durable steel guard.



Optional push bar keeps limbs away from the cab to protect the operator (STP25 only).



Angled jaw tips aide in digging roots and loosening soil around the base of trees.

	STP15	STP25
Weight (kg)	228 lbs (103.4)	316 lbs (143.3) without push bar
Jaw Opening (cm)	10" (25.4) Maximum	
Jaw Construction	Teeth (cm)	Laser cut from 5/8" (1.6) steel x 16" (40.6) long
	Tips	Angled for digging
Jaw Pivot Pin (cm)	Greasable pin constructed of solid 2-1/2" (6.4) diameter steel	Greasable pin constructed of solid 1-1/4" (3.175) diameter steel
Hydraulic Cylinder (cm)	2" x 8" 1-1/8" (5.1x20.3x2.9) Welded hydraulic cylinder	
Hydraulic Cylinder Pivot Pins	Greasable	
Cylinder Guards (cm)	3/16" (5) Welded steel plate	
Max. Pressure Rating (mPa)	3500 psi (24.1)	