

**RBT55120 Model**

List	Specifications & Capacities
<b>Blade width</b>	120"
<b>Approximate weight (lb) with manual links</b>	1753 lb
<b>Horsepower rating</b>	90-180
<b>Maximum G.V.W. (lb)</b>	15,000
<b>Hitch type</b>	Cat. 2 & 3 (Fits Land Pride Quick Hitch)
<b>Blade angle, hydraulic operated</b>	Up to 45° clockwise and counterclockwise with blade facing forward or reversed
<b>Angle cylinder</b>	4 1/2" x 16" x 2"
<b>Blade offset, hydraulic operated</b>	Up to 33" left and right
<b>Offset cylinder</b>	4 1/2" x 16" x 2"
<b>Blade tilt, hydraulic operated</b>	Maximum 15° up and 15° down with blade facing forward or reversed
<b>Tilt cylinder</b>	3" x 8" x 1 1/4"
<b>Moldboard height</b>	19"
<b>Moldboard thickness</b>	5/16" with reinforced channel
<b>Cutting edge</b>	1/2" x 6" Heat treated, replaceable & reversible (double bevel)
<b>Main frame</b>	Fully enclosed welded, formed box
<b>Park stand</b>	Retractable
<b>Accessories</b>	Single or dual gauge wheel, (manual or hydraulic), skid shoes, end plates, hardened wear edge plates, double selector valve, manual angle link, manual offset link, and manual tilt link