

FDR25 Series Rear Discharge Mowers

Specifications & Capacities		
Model Numbers	FDR2572	FDR2584
Maximum Horsepower - Engine	60 horsepower (44.7kW)	
Cutting Width	72" (1.83m)	84" (2.13m)
Overall Width	75" (1.90m)	87" (2.20m)
Height	Minimum: 35 1/2" (.93m) / Maximum: 41" (1.04m)	
Length	69" (1.75m)	75" (1.91m)
Weight	718 lbs (325.7 kg)	812 lbs (368.3 kg)
Cutting Height [1/2" (13mm) increments]	3/4" - 5 1/4" (19cm - 13.3cm)	
Deck Material Thickness	3/16" (5mm)	
Blade Tip Speed	18,130 FPM (92.1mps)	17,210 FPM (87.4mps)
Blades Construction - 3 each	1/4" x 2 1/2" x 25" Heat Treated Alloy Steel	5/16" x 2 1/2" x 29" Heat Treated Alloy Steel
Blade Options	Standard Blades: Medium Lift Optional Blades: Low Lift, High Lift & Mulching	
Blade Overlap	1 1/4" (32mm)	
Blade Spindles	Greasable	
Discharge	Rear	
Hitch	Category 1	
Lower Hitch	Floating & Adjustable Clevis with Plated Pins	
Top Link	Floating & Adjustable Clevis	
Caster Gauge Wheels	3 1/4" x 10" Solid Rubber	4" x 11" Semi Solid
Caster Wheel Spindle	1" Diameter with Greasable Bushing	
Drive Train	540 rpm power take-off Cast Iron Housing Gearbox With Beveled Gears, 1:2.83 Ratio Spring Loaded Single V-Belt	
Gearbox Oil Capacity & Type	3.5 Pints of 80-90W EP Gear Lube	
Driveline	Heavy-duty w/ quick coupler	
Front Roller	Optional	
Quick Hitch Compatible	Fits Land Pride Quick Hitch	

26761

