

FDR3690 Rear Discharge Mower

Specifications & Capacities		FDR3690
Tractor Horsepower Rating	hp (kW)	30-70 (22.4 - 52.2)
Cutting Width	inch (m)	90 (2.29)
Overall Width	inch (m)	92 (2.34)
Overall Height	inch (m)	38 1/8 (.97)
Overall Length	inch (m)	85 7/8 (2.18)
Weight Without Front Roller	lbs (kg)	930 (421.8)
Front Roller	lbs (kg)	Optional, Weight = 6 (2.7)
Cutting Height	inch (mm)	1 (25) to 6 1/2 (165) in 1/4 (6) increments with plated spacers
Deck Material Thickness	inch (mm)	3/16 (5)
Blade Tip Speed	fpm (mps)	16,500 (83.8)
Blades Construction - 6 each		Free swinging, 1/4" x 2 1/2" x 14" Hardened, Medium Lift (2 per blade spindle)
Blade Overlap	inch (cm)	2 (5.1)
Blade Spindles		1 3/8" Stress-Proof Shaft
Deck Spindle Housings		Cast Iron Greasable Hubs
Belt		Double V Powerband Belt
Belt Take-Up		Spring Loaded Idler
Gearbox		540 rpm Cast Iron Housing Gearbox With Beveled Gears, 1:2.75 Ratio
Gearbox Oil Capacity & Type	pints (L)	3.5 (1.66) of 80-90W EP Gear Lube
Discharge		Rear
Hitch		Category I
Quick Hitch Compatible		Fits Land Pride Quick Hitch
Lower Hitch		Floating Clevis with Plated Pins
Top Link		Floating Clevis
Castered Gauge Wheels		5" x 13" Semi-Solid Tire with Bearings
Caster Wheel Spindle		1 1/4" Diameter with Greasable Bushing
Driveline		Heavy-Duty Cat. 4 W/Quick Coupler

