

HRS3025

Specifications & Capacities		
Minimum tractor horsepower		52 hp
Maximum hydraulic horsepower output		43 hp
Pump capacity		Approx. 25 gpm @ 540 rpm at 3000 PSI
PTO input speed		540 rpm
Hydraulic fluid type		Mobil Fluid 424 (See www.mobil.com for alternate fluids)
Reservoir capacity		35 Gallons
Filter type		LE 10 Micron filter
Oil level check		Oil fill cap with dipstick
Overload protection		Hydraulic relief valve
Hitch		3-Point Cat. I & II with clevis style lower hitch, Quick hitch adaptable
Driveline		ASAE Category 2
Pressure & return hose lengths		24 Feet each
Case drain port		3/4"-16 UNF
Optional & Accessory Equipment		
Flow control	Option	No Valve No Cooler (Pressure relief valve provided for protection)
	Option	No Valve With Cooler (Pressure relief valve provided for protection)
	Option	Manual Operated Valve With Oil Cooler (Pressure relief is built into the valve)
	Option	Solenoid Operated Valve With Oil Cooler (Pressure relief is built into the valve)
Small flat face couplers	Option	1/2" body size (Includes adapter for attaching to hoses with 1 5/16" threads)
Large flat face couplers	Option	3/4" body size (Attach to hoses with 1 5/16" threads)
Case drain kit	Option	Complete with 3/4" MORB x 9/16" MJIC elbow, 23'-9" of 3/8" hydraulic hose, and one 3/8" body flat face low spill quick coupler male tip

