

PFL & PFLE Series

Specifications & Capacities								
Model Numbers	PFL			PFLE			PFL & PFLE	
	2042	3042	3048	4548	5548	5560	6448	6460
Side Step								
Universal Quick Attach Hitch	Yes	Yes	Yes	No	No	No	Yes	Yes
Euro Hitch	No	No	No	Yes	Yes	Yes	Yes	Yes
Weight								
lbs (kg)								
Universal Quick Attach Hitch	301 (136.5)	340 (154.2)	358 (162.4)	N/A	N/A	N/A	686 (311.2)	744 (337.5)
Euro Hitch	N/A*	N/A*	N/A*	422 (194.4)	446 (202.3)	492 (223.2)	683 (309.8)	741 (336.1)
Lift Capacity								
lbs (kg)	2100 (952.5)	3000 (1360.8)		4500 (2041.2)	5500 (2494.8)		6400 (2903)	
in (cm)	Lift capacity is based on load being 24 (61) from face of Frame (Cross bar). Load must be palletized and supported by two forks.							
Class	II			II			III	
Frame Width	45 7/8 (1.17)			45 7/8 (1.17)			60 1/2 (1.54)	
Frame Height	37 1/2 (.95)			37 1/2 (1.02)	40 (1.02)	40 (1.02)		41 1/8 (1.04)
Tine Thickness	1 (2.5)	1 1/4 (3.2)	1 1/4 (3.2)	1 1/2 (3.8)		1 3/4 (4.4)		1 3/4 (4.4)
Tine Width	3 (8)	4 (10)	4 (10)		4 (10)		4 3/4 (12)	
Tine Length	42 (1.07)		48 (1.22)		48 (1.22)	60 (1.52)	48 (1.22)	60 (1.52)
Fork Positioning Lock	Spring Loaded Toggle							

