

**GB30 Series**

Specifications & Capacities				
		GB3068	GB3074	GB3080
Weight (without shields and optional cutting edge)	lbs (kg)	969 (440)	1007 (457)	1074 (487)
Width	in (m)	69 (1.75)	75 (1.91)	81 (2.06)
Closed height	in (cm)	33 (83.8)		
Grapple jaw opening	in (m)	40 1/2 (1.03)		
Hitch type		Universal Quick Attach		
Hose couplers	in (cm)	One - 1 1/16 (2.7) FORB male and One - 1 1/16 (2.7) FORB female flat faced couplers		
Bucket floor thickness	in (mm)	1/4 (6)		
Bucket side wall thickness	in (mm)	1/2 (13)		
Bucket cutting edge thickness	in (mm)	3/4 (19)	3/4 (19)	1 (25)
Working depth of bucket	in (m)	37 1/2 (.95)		
Number of upper grapple jaws		2		
Upper grapple tooth thickness	in (mm)	3/4 (19)		
Upper grapple jaw pivot pins	in (cm)	Greasable 1 1/4 (3.2) pivot pins		
Hydraulic cylinders	in (cm)	Two - 2 1/2 x 8 x 1 1/4 (6.4 x 20.3 x 3.2) Rod		
Hydraulic cylinder pivot pins	in (cm)	Greasable 1 (2.5) pivot pins		
Maximum hydraulic pressure	psi (KPa)	3500 (24132)		
Optional bolt-on cutting edge		Reversible and replaceable		
Optional hose shields	in (mm)	1/4 (6) Welded housing with 1/4 (6) removable cover		
Optional cylinder shields	in (mm)	5/16 (8) Formed channels		

